R 455A

30.05.2024 30.05.2024 Print date Revision date Version 2.0 (en) replaces version of 13.10.2020 (1.0)



* SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation R 455A Art-Nr(n). 0087

Unique Formula Identifier UFI: YX2S-J0S9-C00A-SAWD

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Refrigerant

* 1.3 Details of the supplier of the safety data sheet

Supplier GHC Gerling, Holz & Co. Handels GmbH Ruhrstraße 113 D-22761 Hamburg Telephone +49 40 853 123 0 E-mail hamburg@ghc.de Website www.ghc.com

Department responsible for information: GHC Gerling, Holz & Co. Handels GmbH Telephone +49 40 853 123 0

E-mail (competent person): msds@ghc.de

* 1.4 Emergency telephone number

EN: Poison Information Center Mainz +49 6131 19240

* SECTION 2: Hazards identification

* 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 Classification procedure

[CLP]

Flam. Gas 1B, H221 Press. Gas (Liq.), H280

Hazard statements for physical hazards

H221 Flammable gas.

H280 Contains gas under pressure; may explode if heated.

* 2.2 Label elements

* Labelling according to Regulation (EC) No 1272/2008 [CLP]

Hazard pictograms



GHS02

Signal word

Danger

Hazard statements

H221 Flammable gas.

H280 Contains gas under pressure; may explode if heated.

R 455A

30.05.2024 30.05.2024 Print date Revision date Version 2.0 (en) replaces version of 13.10.2020 (1.0)



the chemical gas specialist

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 In case of leakage, eliminate all ignition sources.

P403 Store in a well-ventilated place.

Supplemental hazard information

EIGA0357 Asphyxiant in high concentrations. EIGA0787 Contains fluorinated greenhouse gases.

Please return container with residual pressure.

Withdrawal out of the liquid phase only.

* 2.3 Other hazards

Adverse human health effects and symptoms

Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

The inhalation of gas / vapour in high concentrations may cause cardiac arrhythmia.

Contact with liquid may cause cold burns/frostbite.

Other adverse effects

The substance/mixture does not contain components identified as having endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more.

Results of PBT and vPvB assessment

The substance/mixture does not contain components meeting the PBT/vPvB criteria of the Reach Regulation, Annex XIII, at levels of 0.1% or higher.

* SECTION 3: Composition / information on ingredients

3.1 Substances

not applicable

* 3.2 Mixtures

Hazardous ingredients

	•						
CAS No	EC No	Index No	Substance name	Concentration	Classification according to Regulation (EC) No 1272/2008 [CLP]	SCL/ M/ ATE	
754-12-1	468-710-7		2,3,3,3-Tetrafluoroprop- 1-ene (R 1234yf)	73.5 - 77.5 weight-%	Flam. Gas 1B; H221 Press. Gas (Liq.); H280	ATE(inhalation gas): > 405000 ppm	
75-10-5	200-839-4		Difluoromethane (R 32)	19.5 - 22.5 weight-%	Flam. Gas 1B; H221 Press. Gas (Liq.); H280		
124-38-9	204-696-9		Carbon dioxide	2 - 5 weight-%	Press. Gas (Liq.); H280		
REACH No		Substand	ce name				
01-0000019665-61		2,3,3,3-T	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)				
01-2119471	1312-47	Difluoron	nethane (R 32)				
-		Carbon o	dioxide				

The text of the H-and EUH-phrases is shown in section 16.

Carbon dioxide does not require registration according to Article 2 (7) in conjunction with Annex IV / V of the Regulation (EC) No 1907/2006 [REACH].

R 455A

30.05.2024 30.05.2024 Print date Revision date 2.0 (en) Version replaces version of 13.10.2020 (1.0)



SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Remove contaminated, saturated clothing immediately. In the event of persistent symptoms obtain medical treatment. First aider: Pay attention to self-protection!

Following inhalation

Remove casualty to fresh air and keep warm and at rest.

In case of respiratory standstill give artificial respiration by respiratory bag (Ambu bag) or respirator. Obtain medical assistance.

Following skin contact

In case of skin contact rinse with warm water.

In case of frostbite, wash with plenty of water; do not remove clothing.

In case of frostbite rinse with lukewarm (not hot) water for at least 15 minutes. Do not remove clothing frozen to the skin. Thaw with lukewarm water. Apply a sterile dressing. Obtain medical assistance.

After eve contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical assistance.

Following ingestion

Ingestion is not considered a potential route of exposure.

* 4.2 Most important symptoms and effects, both acute and delayed

SymptomsThe following symptoms may occur in case of strong exposition:

Unconsciousness

Cardiac arrhythmias

Dizziness

Nausea

Headache

Effects

Long-term inhaling of separation products may cause pulmonary oedema.

* 4.3 Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically.

* SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguishing powder alcohol resistant foam Water spray jet

Unsuitable extinguishing media

Carbon dioxide (CO2)

Full water jet

* 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products In case of fire formation of dangerous gases possible. Carbon monoxide Carbon dioxide (CO2) Hydrogen fluoride Carbonyl fluoride

R 455A

30.05.2024 30.05.2024 Print date Revision date Version 2.0 (en) replaces version of 13.10.2020 (1.0) GERLIN HOLZ+C

the chemical gas specialist

5.3 Advice for firefighters

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

If possible, shut off gas valves and move containers to a safe location.

Use water spray jet to protect personnel and to cool endangered containers.

Exposure to fire may cause rupture / explosion of the containers.

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Dispose of fire residues and contaminated extinguishing water in accordance with local, official regulations.

* SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Use personal protection equipment.

Leave the danger area.

Keep people away and stay on the upwind side.

For emergency responders
Personal protection by wearing close-fitting protective clothing and breathing apparatus.
Pay attention to extension of gas especially at ground (heavier than air) and in direction of the wind.

Remove persons to safety.

Eliminate all ignition sources if safe to do so.

* 6.2 Environmental precautions

If possible, stop flow of product.

Do not allow to enter into soil/subsoil.

Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For containment

If necessary, secure leaky pressure receptacles using a salvage container.

Prevent the liquid from spreading over a wide area (set up barriers, cover sewage systems).

Limit expansion of the gas (water spray jet).

For cleaning up

Leave to vapourize.

Provide adequate ventilation.

* 6.4 Reference to other sections

Disposal: see section 13

Personal protection equipment: see section 8

* SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Use only in well-ventilated areas.
Transfer and handle product only in closed systems.

Usual measures for fire prevention.

Containers' temperature should not be increased above 50 °C.

The working pressure in the receptacle must not exceed the saturation vapour pressure of the pure product resulting at a temperature of 50 °C

Prevent cylinders from falling over.

Take precautionary measures against static discharges. Ground barrels and installations. Use only antistatically equipped (spark-free) tools.

Ùse explosion-proof machinery, apparatus, ventilation facilities, tools etc.

Ensure valve protection device is correctly fitted.

Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

Open valve slowly to avoid pressure shock.

Do not allow backflow into the container.

Entering of water into the container must be prevented.

No water to valves, flanges and other fittings.

Purging of pipes and valves with inert gases - to avoid: water, solvents.

R 455A

30.05.2024 30.05.2024 Print date Revision date Version 2.0 (en) replaces version of 13.10.2020 (1.0)



Advices on general occupational hygiene When using do not eat, drink, smoke, sniff.

Wash hands before breaks and after work.

Remove contaminated clothing and protective equipment before entering eating areas.

* 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

All regulations and local requirements for the storage of containers have to be respected.

Keep container tightly closed and in a well-ventilated place.

Containers' temperature should not be increased above 50 °C.

Prevent cylinders from falling over.

Only use containers specifically approved for the substance/product.

Information on suitable materials for receptacles and valves see ISO 11114.

Materials to avoid

Do not store together with explosives.
Do not store together with flammable liquids.
Do not store together with flammable solids.

Do not store together with pyrophoric and self-heating substances.

Do not store together with oxidizing liquids or oxidizing solids.

Do not store together with toxic liquids or toxic solids.

Do not store together with infectious substances. Do not store together with radioactive material.

Do not store together with food or feed.

* 7.3 Specific end use(s)

Recommendation

An exposure scenario is not required.

* SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

CAS No	EC No	Substance name	occupational exposure limit value
124-38-9	204-696-9	Carbon dioxide	5000 [ml/m³(ppm)] 9000 [mg/m³] (IE)

DNEL worker

CAS No	Substance name	DNEL value	DNEL type	Remark
75-10-5	Difluoromethane (R 32)	7035 mg/m³	long-term inhalative (systemic)	Assessment factor 7.5, assessment factor.
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	950 mg/m³	long-term inhalative (systemic)	
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	186400 mg/m³	acute inhalative (systemic)	Assessment factor 5

DNEL Consumer

CAS No	Substance name	DNEL value	DNEL type	Remark
75-10-5	Difluoromethane (R 32)	750 mg/m³	long-term inhalative (systemic)	Assessment factor 25, assessment factor.
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	113.1 mg/m³	long-term inhalative (systemic)	Assessment factor 2, assessment factor.
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	186400 mg/m³	acute inhalative (systemic)	Assessment factor 5, assessment factor.

PNEC

CAS No	Substance name	PNEC Value	PNEC type	Remark
75-10-5	Difluoromethane (R 32)	0.313 mg/L	aquatic, freshwater	Assessment factor 1000, assessment factor.
75-10-5	Difluoromethane (R 32)	1.807 mg/kg dw	sediment, freshwater	

R 455A

30.05.2024 30.05.2024 Print date Revision date 2.0 (en) 13.10.2020 (1.0) Version replaces version of



the chemical gas specialist

CAS No	Substance name	PNEC Value	PNEC type	Remark
75-10-5	Difluoromethane (R 32)	3.13 mg/L	aquatic, intermittent release	Assessment factor 100
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	0.01 mg/L	aquatic, marine water	Assessment factor 10000, assessment factor.
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	0.1 mg/L	aquatic, freshwater	Assessment factor 1000, assessment factor.
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	0.151 mg/kg dw	sediment, marine water	
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	1 mg/L	aquatic, intermittent release	Assessment factor 100
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	1.49 mg/kg	soil	
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	1.51 mg/kg dw	sediment, freshwater	

* 8.2 Exposure controls

Appropriate engineering controls

Technical measures to prevent exposure Transfer and handle only in enclosed systems.

Personal protection equipment

Eye/face protectionProtective goggles according to EN 166, in case of increased risk add protective face shield.

Hand protection

Safety gloves according to EN 388:

Chromate-free leather

Body protection: Safety shoes with steel toecap.

Body covering work clothing or chemical resistant suit at increased risk.

Respiratory protection Keep self contained breathing apparatus readily available for emergency use.

Respiratory protection necessary at:

high concentrations

Respiratory protection complying with EN 137.

Do not use any filter apparatus.

In case of rescue and maintenance activities in storage containers use environment-independent breathing apparatus because of risk of suffocation due to displacement of oxygen.

Thermal hazards

Use cold-resistant protective equipment.

Environmental exposure controls

Prevent release to the environment.

* SECTION 9: Physical and chemical properties

* 9.1 Information on basic physical and chemical properties

Physical state

Gaseous / liquefied under pressure.

Colour

colourless

Odour

perceptible

R 455A

Print date 30.05.2024
Revision date 30.05.2024
Version 2.0 (en)
replaces version of 13.10.2020 (1.0)



the chemical gas specialist

Safety relevant basis data

Method	Course Demark
Method	Source, Remark
	not determined
	not applicable
	Information concerns main component.
	Flammable gas (H221).
	not applicable
	Information concerns main component.
	No decomposition if used as directed.
	not applicable
	not applicable
	Information concerns main component.
	Information concerns main component.
	not applicable
	Information concerns main component.
	not applicable

* 9.2 Other information

* Information with regard to physical hazard classes

* Gases under pressure

Safety characteristics

	Value	Method, Result	Source, Remark
Critical temperature	82.8 °C		

* Other information

Vapours are heavier than air.

* SECTION 10: Stability and reactivity

* 10.1 Reactivity

May form an explosive mixture with air.

* 10.2 Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

* 10.3 Possibility of hazardous reactions

Must not be mixed with air or oxygen.

Danger of fire and explosion with oxidants, alkali metals and earth alkali metals.

* 10.4 Conditions to avoid

Heat sources / heat - risk of bursting.

Ignition sources, open flames, glowing metal surfaces, etc.

R 455A

Print date 30.05.2024
Revision date 30.05.2024
Version 2.0 (en)
replaces version of 13.10.2020 (1.0)



* 10.5 Incompatible materials

Alkali metals Alkaline earth metal Powdered metals Oxidising agent, strong

10.6 Hazardous decomposition products

When handled and stored appropriately, no dangerous decomposition products are known.

* SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

* Animal data

	Effective dose	Method, Evaluation	Source, Remark
Acute oral toxicity			Study technically not feasible.
Acute dermal toxicity			Study technically not feasible.
Acute inhalation toxicity	CAS No754-12-1 2,3,3,3- Tetrafluoroprop-1-ene (R 1234yf) Acute inhalation toxicity (gas) LC50: > 405000 ppm Species Rat Exposure time 4 h	OECD 403	

* Assessment/classification

Based on available data, the classification criteria are not met.

* Skin corrosion/irritation

Other information

Study technically not feasible.

* Serious eye damage/irritation

* Other information

Study technically not feasible.

* Sensitisation to the respiratory tract

* Assessment/classification

No data available

* Skin sensitisation

* Other information

Study technically not feasible.

* Germ cell mutagenicity

	Value	Method	Result / Evaluation	Remark
In vitro mutagenicity/genotox icity		OECD 473	negative	Information concerns main component.
In vivo mutagenicity/genotox icity		OECD 474	negative	Information concerns main component.

* Assessment/classification

Based on available data, the classification criteria are not met.

R 455A

30.05.2024 30.05.2024 Print date Revision date 2.0 (en) 13.10.2020 (1.0) Version replaces version of



Carcinogenicity

Other information

No data available

* Reproductive toxicity

Animal data

	Value	Method	Result / Evaluation	Remark
Reproductive toxicity	inhalative NOAEC 50000 ppm Species Rat	OECD 416		Information concerns main component.

Assessment/classification

Based on available data, the classification criteria are not met.

* STOT-single exposure

STOT SE 1 and 2

Assessment/classificationBased on available data, the classification criteria are not met.

* STOT-repeated exposure

Assessment/classification

Based on available data, the classification criteria are not met.

Aspiration hazard

Assessment/classification Study technically not feasible.

11.2 Information on other hazards

Additional information

The inhalation of gas / vapour in high concentrations may cause cardiac arrhythmia. Inhalation causes narcotic effects/intoxication.

Other information

The product has not been tested. The information is derived from the properties of the individual components.

* SECTION 12: Ecological information

* 12.1 Toxicity

Aquatic toxicity

	Effective dose	Method, Evaluation	Source, Remark
Acute (short-term) fish toxicity	LC50: > 197 mg/L Species Cyprinus carpio (Common Carp) Test duration 96 h	OECD 203	Information concerns main component.
Chronic (long-term) fish toxicity	not determined		
Acute (short-term) toxicity to crustacea	EC50 > 100 mg/L Species Daphnia magna (Big water flea) Test duration 48 h	OECD 202	Information concerns main component.
Chronic (long-term) toxicity to aquatic invertebrate	not determined		
Acute (short-term) toxicity to algae and cyanobacteria	EC50 > 100 mg/L Species Raphidocelis subcapitata Test duration 72 h	OECD 201	Information concerns main component.
Chronic (long-term) toxicity to aquatic algae and cyanobacteria	not determined		
Toxicity to other aquatic plants/organisms	not determined		

R 455A

30.05.2024 30.05.2024 Print date Revision date Version 2.0 (en) replaces version of 13.10.2020 (1.0)



Tetrafluoroprop-1-ene (R

1234yf)

Effective dose Method, Evaluation Source, Remark Toxicity to microorganisms not determined * 12.2 Persistence and degradability Value Method Source, Remark Biodegradation Degradation rate 5 % **OECD 301 D** CAS No75-10-5 Test duration 28 d Difluoromethane (R 32) Biodegradation Degradation rate < 5 % OECD 301F/ ISO 9408/ CAS No754-12-1 2,3,3,3-

EEC 92/69/V, C.4-D

Test duration 28 d

Assessment/classification

Not readily biodegradable (according to OECD criteria)

* 12.3 Bioaccumulative potential

Assessment/classification

Based on the n-octanol/water partition coefficients of the individual components of the mixture, accumulation in organisms is not expected.

* 12.4 Mobility in soil

	Value	Distribution	Transport type	Method	Remark
Half-life time in soil	CAS No75-10-5 Difluoromethane (R 32) 21.73 L/kg			KOC value	
Half-life time in soil	CAS No754-12-1 2,3,3,3- Tetrafluoroprop- 1-ene (R 1234yf)			KOC value	

* 12.5 Results of PBT and vPvB assessment

The substance/mixture does not contain components meeting the PBT/vPvB criteria of the Reach Regulation, Annex XIII, at levels of 0.1% or higher.

* 12.6 Endocrine disrupting properties

No data available

* 12.7 Other adverse effects

	Value	Method	Source, Remark
Ozone depletion potential (ODP):	0		
Global warming potential (GWP)	146		

Additional ecotoxicological information

Additional information

The product has not been tested. The data are derived from the individual components of the mixture.

SECTION 13: Disposal considerations

* 13.1 Waste treatment methods

Waste codes/waste designations according to EWC/AVV

Waste name Waste code product 140601 * chlorofluorocarbons, HCFC, HFC

Appropriate disposal / ProductWaste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Prevent release to the environment. No disposal via the sewage.

Disposal according to local regulations.

R 455A

Print date 30.05.2024
Revision date 30.05.2024
Version 2.0 (en)
replaces version of 13.10.2020 (1.0)



the chemical gas specialist

Appropriate disposal / Package

Transportable pressure equipment (empty, residual pressure): Return to supplier / manufacturer.

* SECTION 14: Transport information

	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA- DGR)
14.1 UN number or ID number	UN 3161	UN 3161	UN 3161
14.2 UN proper shipping name	LIQUEFIED GAS, FLAMMABLE, N.O.S. (Difluormethan, 2,3,3,3- Tetrafluorpropen)	LIQUEFIED GAS, FLAMMABLE, N.O.S. (Difluoromethane, 2,3,3,3- Tetrafluorprop-1-ene)	Liquefied gas, flammable, n.o.s. (Difluoromethane, 2,3,3,3- Tetrafluorprop-1-ene)
14.3 Transport hazard class(es)	2.1	2.1	2.1
14.4 Packing group	-	-	-
14.5 Environmental hazards	No	No	No

14.6 Special precautions for user

The protective measures listed in Sections 6, 7 and 8 of the Safety Data Sheet have to be considered.

14.7 Maritime transport in bulk according to IMO instruments

No carriage in bulk.

Land transport (ADR/RID)

UN number or ID number UN 3161

UN proper shipping name LIQUEFIED GAS, FLAMMABLE, N.O.S. (Difluormethan, 2,3,3,3-

Tetrafluorpropen)

Transport hazard class(es) 2.1

Hazard label(s) 2.1

Classification code 2F

Packing group
Environmental hazards No

Limited quantity (LQ) 0

Special provisions 274, 662

Tunnel restriction code B/D

* Sea transport (IMDG)

UN number or ID number UN 3161

UN proper shipping name LIQUEFIED GAS, FLAMMABLE, N.O.S. (Difluoromethane, 2,3,3,3-

Tetrafluorprop-1-ene)

Transport hazard class(es) 2.1

Packing group
Environmental hazards No

Limited quantity (LQ) 0

Marine pollutant No

EmS F-D, S-U

* Air transport (ICAO-TI / IATA-DGR)

UN number or ID number UN 3161

UN proper shipping name Liquefied gas, flammable, n.o.s. (Difluoromethane, 2,3,3,3-Tetrafluorprop-1-ene)

Transport hazard class(es) 2.1

R 455A

30.05.2024 30.05.2024 Print date Revision date Version 2.0 (en) 13.10.2020 (1.0) replaces version of



Packing group **Environmental hazards** No

* SECTION 15: Regulatory information

* 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations (EU)

To follow:

Regulation (EU) 2024/573 on fluorinated greenhouse gases.
Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), Annéx XVII No 40.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances.

Regulation (EU) 2015/2068 establishing, pursuant to Regulation (EU) No 517/2014, the format of labels for products and

equipment containing fluorinated greenhouse gases.

Regulation (EU) 2015/2067 establishing, pursuant to Regulation (EU) No 517/2014, ~ certification ~ as regards stationary refrigeration, air conditioning and heat pump equipment, and ~ containing fluorinated greenhouse gases. National and local regulations concerning chemicals shall be observed.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive] VOC VOC-value ≥ 95 %

* 15.2 Chemical Safety Assessment

National regulations

Chemical safety assessments for substances in this mixture were carried out.

SECTION 16: Other information

Abbreviations and acronyms

Flam. Gas 1B: Flammable gas, Category 1B Press. Gas (Liq.): Liquefied gas (LG)

Key literature references and sources for data

Information from our suppliers and data from the "GESTIS Substances Database" and the "Registered Substances" database of the European Chemicals Agency (ECHA) were used to create this safety data sheet.

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP] The mixture was classified by the manufacturer.

Additional information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Relevant H- and EUH-phrases (Number and full text)

H221 Flammable gas.

H280 Contains gas under pressure; may explode if heated.

Indication of changes

Data changed compared with the previous version