1.2-Butadiene

13.05.2024 13.05.2024 Print date Revision date 10.0 (en) Version replaces version of 27.08.2019 (9.0)



the chemical gas specialist

* SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation 1,2-Butadiene

Art-Nr(n). 2205

Substance name 1,2-butadiene **EC No** 209-674-2

REACH No. 01-2119458051-48

CAS No 590-19-2

* 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Use only as an intermediate under strictly controlled conditions.

1.3 Details of the supplier of the safety data sheet

Supplier GHC Gerling, Holz & Co. Handels GmbH D-22761 Hamburg Telephone +49 40 853 123 0 E-mail hamburg@ghc.de Website www.ghc.com

Department responsible for information: GHC Gerling, Holz & Co. Handels GmbH Telephone +49 40 853 123 0

E-mail (competent person): msds@ghc.de

* 1.4 Emergency telephone number

EN: Poison Information Center Mainz +49 6131 19240

* SECTION 2: Hazards identification

* 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Classification procedure

Flam. Gas 1A, H220

Press. Gas (Liq.), H280

Hazard statements for physical hazards H220 Extremely flammable gas. H280 Contains gas under pressure; may explode if heated.

* 2.2 Label elements

* Labelling according to Regulation (EC) No 1272/2008 [CLP]

Hazard pictograms



GHS02

Signal word Danger

1.2-Butadiene

13.05.2024 13.05.2024 Print date Revision date 10.0 (en) Version replaces version of 27.08.2019 (9.0)



the chemical gas specialist

Hazard statements

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 In case of leakage, eliminate all ignition sources. P403 Store in a well-ventilated place.

Supplemental hazard information

EIGA0357 Asphyxiant in high concentrations. Please return container with residual pressure.

* 2.3 Other hazards

Adverse human health effects and symptoms

Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level. Contact with liquid may cause cold burns/frostbite.

Other adverse effects

The substance/mixture does not contain components identified as having endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more.

Results of PBT and vPvB assessment

The substance/mixture does not contain components meeting the PBT/vPvB criteria of the Reach Regulation, Annex XIII, at levels of 0.1% or higher.

* SECTION 3: Composition / information on ingredients

3.1 Substances

Substance name 1.2-butadiene **EC No** 209-674-2

01-2119458051-48 REACH No.

CAS No 590-19-2

Additional information

Content: >= 97 %

3.2 Mixtures

not applicable

* SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Remove contaminated, saturated clothing immediately. In the event of persistent symptoms obtain medical treatment.

First aider: Pay attention to self-protection!

Following inhalation

Remove casualty to fresh air and keep warm and at rest.

In case of respiratory standstill give artificial respiration by respiratory bag (Ambu bag) or respirator. Obtain medical assistance.

Following skin contact

In case of skin contact rinse with warm water.

In case of frostbite, wash with plenty of water; do not remove clothing.

In case of frostbite rinse with lukewarm (not hot) water for at least 15 minutes. Do not remove clothing frozen to the skin. Thaw with lukewarm water. Apply a sterile dressing. Obtain medical assistance.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical assistance.

1.2-Butadiene

13.05.2024 13.05.2024 Print date Revision date 10.0 (en) Version replaces version of 27.08.2019 (9.0)



Following ingestion

Ingestion is not considered a potential route of exposure.

* 4.2 Most important symptoms and effects, both acute and delayed

Symptoms

The following symptoms may occur in case of strong exposition: Unconsciousness Dvspnoea Frostbite

4.3 Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically.

To supervise the blood circulation.

* SECTION 5: Firefighting measures

* 5.1 Extinguishing media

Suitable extinguishing media

Water spray jet Extinguishing powder Foam

Unsuitable extinguishing media

Carbon dioxide (CO2) Full water jet

* 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products In case of fire formation of dangerous gases possible. Carbon monoxide Carbon dioxide (CO2)

* 5.3 Advice for firefighters

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

* Additional information

If possible, shut off gas valves and move containers to a safe location.

Use water spray jet to protect personnel and to cool endangered containers.

Exposure to fire may cause rupture / explosion of the containers.

Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.

Dispose of fire residues and contaminated extinguishing water in accordance with local, official regulations.

* SECTION 6: Accidental release measures

* 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Use personal protection equipment.

Leave the danger area.

Keep people away and stay on the upwind side.

For emergency responders

Personal protection by wearing close-fitting protective clothing and breathing apparatus.

Pay attention to extension of gas especially at ground (heavier than air) and in direction of the wind.

Remove persons to safety.

Eliminate all ignition sources if safe to do so.

* 6.2 Environmental precautions

If possible, stop flow of product.

Do not allow to enter into soil/subsoil.

Do not allow to enter into surface water or drains.

1.2-Butadiene

13.05.2024 13.05.2024 Print date Revision date 10.0 (en) Version 27.08.2019 (9.0) replaces version of



6.3 Methods and material for containment and cleaning up

For containment

If necessary, secure leaky pressure receptacles using a salvage container.

Prevent the liquid from spreading over a wide area (set up barriers, cover sewage systems).

Limit expansion of the gas (water spray jet).

For cleaning up

Leave to vapourize.

Provide adequate ventilation.

* 6.4 Reference to other sections

Disposal: see section 13

Personal protection equipment: see section 8

* SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Use only in well-ventilated areas.

Transfer and handle product only in closed systems.

Usual measures for fire prevention.

Containers' temperature should not be increased above 50 °C.

The working pressure in the receptacle must not exceed the saturation vapour pressure of the pure product resulting at a temperature of 50 °C

Prevent cylinders from falling over.

Take precautionary measures against static discharges. Ground barrels and installations. Use only antistatically equipped (spark-free) tools.

Ùse explosion-proof machinery, apparatus, ventilation facilities, tools etc.

Ensure valve protection device is correctly fitted.

Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

Open valve slowly to avoid pressure shock.

Do not allow backflow into the container.

Entering of water into the container must be prevented.

No water to valves, flanges and other fittings.
Purging of pipes and valves with inert gases - to avoid: water, solvents.

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff.

Wash hands before breaks and after work.

Remove contaminated clothing and protective equipment before entering eating areas.

* 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

All regulations and local requirements for the storage of containers have to be respected.

Keep container tightly closed and in a well-ventilated place.

Containers' temperature should not be increased above 50 °C.

Prevent cylinders from falling over.

Only use containers specifically approved for the substance/product.

Information on suitable materials for receptacles and valves see ISO 11114.

Materials to avoid

Do not store together with explosives.
Do not store together with flammable liquids.

Do not store together with flammable solids.

Do not store together with pyrophoric and self-heating substances. Do not store together with oxidizing liquids or oxidizing solids.

Do not store together with toxic liquids or toxic solids. Do not store together with infectious substances.

Do not store together with radioactive material.

Do not store together with food or feed.

7.3 Specific end use(s)

Recommendation

Use only as an intermediate under strictly controlled conditions.

An exposure scenario is not required.

1,2-Butadiene

13.05.2024 13.05.2024 Print date Revision date 10.0 (en) Version replaces version of 27.08.2019 (9.0)



* SECTION 8: Exposure controls/personal protection

* 8.1 Control parameters

DNEL worker

CAS No	Substance name	DNEL value	DNEL type	Remark
590-19-2	1,2-butadiene	371 mg/m³	long-term inhalative (systemic)	Assessment factor 3
DNEL Con	sumer			
CAS No	Substance name	DNEL value	DNEL type	Remark
590-19-2	1,2-butadiene	79 mg/m³	long-term inhalative (systemic)	Assessment factor 5

* 8.2 Exposure controls

Appropriate engineering controls

Technical measures to prevent exposure
Transfer and handle only in enclosed systems.
Use only as an intermediate under strictly controlled conditions.

Personal protection equipment

Eye/face protection

Protective goggles according to EN 166, in case of increased risk add protective face shield.

Hand protection

Safety gloves according to EN 374: NBR (Nitrile rubber)

Body protection:

Safety shoes with steel toecap.

Body covering work clothing or chemical resistant suit at increased risk.

Respiratory protection

Keep self contained breathing apparatus readily available for emergency use.

Respiratory protection necessary at: high concentrations

Respiratory protection complying with EN 137.

Short term: filter apparatus, filter AX

In case of rescue and maintenance activities in storage containers use environment-independent breathing apparatus because of risk of suffocation due to displacement of oxygen.

Thermal hazards

Use cold-resistant protective equipment.

Environmental exposure controls

Remark

Prevent release to the environment.

* SECTION 9: Physical and chemical properties

* 9.1 Information on basic physical and chemical properties

Physical state

Gaseous / liquefied under pressure.

Colour

colourless

Odour

sweetish

1,2-Butadiene

Print date 13.05.2024
Revision date 13.05.2024
Version 10.0 (en)
replaces version of 27.08.2019 (9.0)



not applicable

Safety relevant basis data

Safety relevant basis data			
	Value	Method	Source, Remark
Odour threshold:			not determined
Melting point/freezing point			not applicable
Boiling point or initial boiling point and boiling range	10.8 °C		
flammability			Extremely flammable gas (H220).
Lower and upper explosion limit	Upper explosion limit 18.3 Vol-%		
Lower and upper explosion limit	Lower explosion limit 1.6 Vol-%		
Flash point			not applicable
Auto-ignition temperature	340 °C		
Decomposition temperature			No decomposition if used as directed.
pH			not applicable
Viscosity			not applicable
Solubility(ies)	Water solubility 0.1 g/L (20°C)		
Partition coefficient n-octanol/water (log value)	1.99 (20°C)		Calculated
Vapour pressure	1410 hPa (20°C)		
Density and/or relative density			not applicable
Relative vapour density	1.95		air = 1

* 9.2 Other information

* Information with regard to physical hazard classes

* Gases under pressure

Safety characteristics

particle characteristics

-	Value	Method, Result	Source, Remark	
Critical temperature	170.6 °C			

* Other information

Vapours are heavier than air.

* SECTION 10: Stability and reactivity

* 10.1 Reactivity

Formation of explosive gas mixtures in contact with air.

* 10.2 Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

* 10.3 Possibility of hazardous reactions

Danger of polymerisation Formation of explosive mixtures with: Air Oxidising agent

* 10.4 Conditions to avoid

Heat sources / heat - risk of bursting. Ignition sources, open flames, glowing metal surfaces, etc.

1,2-Butadiene

13.05.2024 13.05.2024 Print date Revision date 10.0 (en) Version replaces version of 27.08.2019 (9.0)



10.5 Incompatible materials

Oxidising agent Oxygen

* 10.6 Hazardous decomposition products

When handled and stored appropriately, no dangerous decomposition products are known.

* SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Animal data

	Effective dose	Method,Evaluation	Source, Remark
Acute oral toxicity			Study technically not feasible.
Acute dermal toxicity			Study technically not feasible.
Acute inhalation toxicity	Acute inhalation toxicity (gas) > 8000 ppm Species Rat Exposure time 4 h	EU Method B.2	

Assessment/classificationBased on available data, the classification criteria are not met.

Skin corrosion/irritation

Other information

Study technically not feasible.

* Serious eye damage/irritation

Other information

Study technically not feasible.

* Sensitisation to the respiratory tract

Other information

No data available

* Skin sensitisation

Other information

Study technically not feasible.

* Germ cell mutagenicity

	Value	Method	Result / Evaluation	Remark
In vitro mutagenicity/genoto	x	OECD 471 (Ames Test)	negative	

Assessment/classification

Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment/classification

No data available

* Reproductive toxicity

1,2-Butadiene

Print date 13.05.2024
Revision date 13.05.2024
Version 10.0 (en)
replaces version of 27.08.2019 (9.0)



Animal data

	Value	Method	Result / Evaluation	Remark
Reproductive toxicity	inhalative NOAEC 6000 ppm Species Rat	OECD 421		

* Assessment/classification

Based on available data, the classification criteria are not met.

* STOT-single exposure

* STOT SE 1 and 2

* Assessment/classification

Based on available data, the classification criteria are not met.

* STOT-repeated exposure

* Animal data

	Effective dose	Method	Specific effects:	Organs affected:	Source, Remark
Inhalative specific target organ toxicity (repeated exposure)	NOAEL(C): 1000 ppm Species Rat (male / female) Exposure time 2 a Exposure frequency 6 h/d	OECD 453			Analogous to a similar product.

* Assessment/classification

Based on available data, the classification criteria are not met.

* Aspiration hazard

* Remark

Study technically not feasible.

11.2 Information on other hazards

* Other information

May cause frostbite.

* SECTION 12: Ecological information

* 12.1 Toxicity

Aquatic toxicity

	Effective dose	Method,Evaluation	Source, Remark
Acute (short-term) fish toxicity	LC50: 42.54 mg/L Species Fish Test duration 96 h	QSAR	
Chronic (long-term) fish toxicity	not determined		
Acute (short-term) toxicity to crustacea	EC50 7.3 mg/L Species Daphnia magna (Big water flea) Test duration 48 h	OECD 202	
Chronic (long-term) toxicity to aquatic invertebrate	not determined		
Acute (short-term) toxicity to algae and cyanobacteria	EC50 11.32 mg/L Species Algae Test duration 48 h	QSAR	
Chronic (long-term) toxicity to aquatic algae and cyanobacteria	not determined		
Toxicity to other aquatic plants/organisms	not determined		

1,2-Butadiene

13.05.2024 13.05.2024 Print date Revision date 10.0 (en) Version replaces version of 27.08.2019 (9.0)



	Effective dose	Method,Evaluation	Source, Remark
Toxicity to microorganisms	not determined		
* 12.2 Persistence and degradability			
	Value	Method	Source, Remark
Biodegradation	Degradation rate 50 % Test duration 2.36 d	QSAR	

Assessment/classification

Readily biodegradable (to OECD criteria)

* 12.3 Bioaccumulative potential

No data available

* 12.4 Mobility in soil

No data available

* 12.5 Results of PBT and vPvB assessment

The substance/mixture does not contain components meeting the PBT/vPvB criteria of the Reach Regulation, Annex XIII, at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

* SECTION 13: Disposal considerations

* 13.1 Waste treatment methods

Waste codes/waste designations according to EWC/AVV

Waste code product	Waste name
160504 *	gases in pressure containers (including halons) containing hazardous substances

Appropriate disposal / Product

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Prevent release to the environment. No disposal via the sewage.

Appropriate disposal / PackageTransportable pressure equipment (empty, residual pressure): Return to supplier / manufacturer.

* SECTION 14: Transport information

	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA- DGR)
14.1 UN number or ID number	UN 1010	UN 1010	UN 1010
14.2 UN proper shipping name	BUTADIENES, STABILIZED	BUTADIENES, STABILIZED	Butadienes, stabilized
14.3 Transport hazard class(es)	2.1	2.1	2.1
14.4 Packing group	-	-	-
14.5 Environmental hazards	No	No	No

14.6 Special precautions for user

The protective measures listed in Sections 6, 7 and 8 of the Safety Data Sheet have to be considered.

14.7 Maritime transport in bulk according to IMO instruments

No carriage in bulk.

1.2-Butadiene

Print date 13.05.2024
Revision date 13.05.2024
Version 10.0 (en)
replaces version of 27.08.2019 (9.0)



Land transport (ADR/RID)

UN number or ID number UN 1010

UN proper shipping name BUTADIENES, STABILIZED

Transport hazard class(es) 2.1

Hazard label(s) 2.1

Classification code 2F

Packing group
Environmental hazards No

Limited quantity (LQ) 0

Special provisions 386, 618, 662, 676

Tunnel restriction code B/D

* Sea transport (IMDG)

UN number or ID number UN 1010

UN proper shipping name BUTADIENES, STABILIZED

Transport hazard class(es) 2.1

Packing group
Environmental hazards No

Limited quantity (LQ) 0

Marine pollutant No

EmS F-D, S-U

* Air transport (ICAO-TI / IATA-DGR)

UN number or ID number UN 1010

UN proper shipping name Butadienes, stabilized

Transport hazard class(es) 2.1
Packing group Environmental hazards No

* SECTION 15: Regulatory information

* 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

* EU legislation

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations (EU)

* To follow:

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), Annex XVII No 40.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances.

National and local regulations concerning chemicals shall be observed.

* Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive] VOC $\,$ VOC-value 97 %

* 15.2 Chemical Safety Assessment

National regulations

For this substance a chemical safety assessment has been carried out.

1,2-Butadiene

13.05.2024 13.05.2024 Print date Revision date 10.0 (en) Version replaces version of 27.08.2019 (9.0)



SECTION 16: Other information

Abbreviations and acronymsFlam. Gas 1A: Flammable gas, Category 1A
Press. Gas (Liq.): Liquefied gas (LG)

Key literature references and sources for data
Information from our suppliers and data from the "GESTIS Substances Database" and the "Registered Substances"
database of the European Chemicals Agency (ECHA) were used to create this safety data sheet.

Additional information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Relevant H- and EUH-phrases (Number and full text)

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

Indication of changes
* Data changed compared with the previous version